



AIR-walker

The AIR-walker is a positive pressure, self-contained, open circuit, compressed air, supplied airline breathing apparatus.

The system can be connected to any airline, cascade air supply hose via the pigtail connection.

Dependant on the end user application, the AIR-walker can select one of three Cam Lock face masks which would best suit that operational use: the FAST-mask, FAST-cowl, or FAST-cape.

For further information refer to the Cam Lock Face Mask Technical Data Sheet.



AIR-walker

TECHNICAL SPECIFICATIONS

Order code	AIRB
Face mask positive pressure	1.7 to 5.9 mbar
Demand valve peak flow rate	>500 litres/min ⁻¹
Harness	Bandolier
Approximate weight	3.0 kg (including face mask)

THERMAL OPERATIONS

Operation temperature	-30°C to +60°C
Maximum humidity	+95%

MATERIALS SPECIFICATIONS

Item	Materials
Harness assembly	Flame retardant polyester
Medium pressure supply hose	Reinforced EPDM
Pigtail hose plug connector	Rectus (CEJN pattern), Foster Hansen and Stäubli

CERTIFICATIONS & APPROVALS

CE 2797, UKCA 0086, EN 14593-1:2018 & BMP 779942, AS/NZS 1716:2012




FAST-mask

FAST-cowl

FAST-cape



Standard head harness with orange tracer for head circumferences less than the 95th percentile



Extra Large (XL) head harness with green tracer for head circumferences above the 95th percentile $\geq 600\text{mm}$

Reference: ISO/TS 16976-2:2015 Respiratory Protective Devices – Human Factors – Part 2: Anthropometrics



AIR-walker
Hard Transit Case

Cam Lock Ltd

10 Springlakes Industrial Estate
Aldershot, Hampshire GU12 4UH
United Kingdom
T: +44 (0)1252 366 648
E: info@camlockuk.com
www.camlocksafety.com